

Project:

P.O.:

LVT-150 150 VA, 1x150 Transformer



Designed specifically for landscape lighting professionals, LVT transformers are solidly built with features like magnetic circuit breakers and stainless steel housings. Rugged enough for the harshest environments, they are backed by warranties from 10 years to a lifetime. With safety and longevity as primary concerns, all Bronzelite transformers are manufactured to meet the stringent UL requirements for landscape lighting applications.

The multiple tap output design allows you to lay simultaneous runs of cable at your preference of 11, 12, 13, 14 or 15 volts, a performance feature which permits complete flexibility in your landscape lighting set-up including compensating for voltage drop.

Dependability and flexibility merge with outstanding warranty protection making Bronzelite's transformers the professional solution for today's landscape lighting specialists.

Due to a program of continuous improvement, Bronzelite reserves the right to make any variation in design or construction to the equipment described.

Any dimension on this sheet is to be assumed a reference dimension and used for information purposes only. It does not govern manufacturing or inspection requirements.

Specifications

Housing:

Housing is dark gray polyester powder-coat formed steel case with stainless steel screws and lockable captive door, hinged on bottom. Enclosed bottom with 1/2" conduit knockouts for indoor mounting. Internal transformer is epoxy encapsulated.

Exterior Mounting:

Transformer should be mounted on the wall, structure, or post in the vertical position. Cable entries should be positioned downward.

Electrical:

6-ft heavy-duty 18-3 AWG, 105° C, SJT power cord with 3 prong grounded wall plug. The transformer is thermally protected and is shielded between the 120V input and the low voltage output, for safety. Insulation type transformers for safe operation.

Euro-Board terminal block for easy low voltage cable attachment. Line voltage amperage draw: 150VA = .9AMP. Optional - 220, 240 or 277 volt, 50/60Hz input. Consult factory for details.

Warranty:

Ten year warranty.

Certification:

UL/cUL Listed to U.S. and Canadian safety standards for wet locations (outdoors).

Dimensions: 7" (H) x 3-1/2" (W) x 3" (D)

Project Notes:

Approval: